



# MOTOTRBO™ SL4010e

## YOU'RE SMARTER, CONNECTED

**With this dynamic evolution of MOTOTRBO digital two-way radios, you're smarter, better connected and more productive. The SL4010e is designed for the manager who needs complete control. With a slim and light form factor incorporating high performance integrated voice and data, this next-generation radio delivers smart connectivity to your organisation.**

### SMART

The MOTOTRBO SL4010e is an ETSI DMR Standards compliant slim and light portable radio that connects you with sophistication. Pocket-sized and with a smooth outline, the radio features a full keypad and 5-line colour screen with a customisable display scheme. The built-in vibrate function alerts you quietly when you need to be discreet, and a comprehensive range of audio accessories allows you to stay connected without disturbing your customers.

### CONNECTED

With integrated voice and data, the SL4010e delivers operation critical communications. Bluetooth® lets you talk without wires, while also enabling precise indoor location-tracking. Powerful audio and advanced noise cancellation ensure your call is heard, even in noisy environments, and 280-character text messaging simplifies complex communications. Integrated Wi-Fi® enables remote software updates, minimising downtime and keeping you connected.

### PRODUCTIVE

With a clear user interface designed to support productivity applications such as Work Order Ticketing, the SL4010e helps your staff make the most of their work day. Voice Announcement and Text-to-Speech allow users to monitor radio settings and text communications hands-free, while sophisticated scan functions keep you in touch with many teams at once.





<b>Model Number</b>	SL4010e
<b>Band</b>	UHF Band 1
<b>GENERAL SPECIFICATIONS</b>	
<b>Frequency</b>	403-470 MHz
<b>High Power Output</b>	3 W
<b>Low Power Output</b>	1 W
<b>Channel Spacing</b>	12.5 kHz
<b>Channel Capacity</b>	1000
<b>Li-ion 2300mAh Battery</b>	
<b>Dimensions with Radio (H x W x D)</b>	121 x 55 x 23 mm
<b>Weight with Radio</b>	174 g
<b>Battery Life<sup>1</sup></b>	14.3 hrs
<b>Power Supply (Nominal)</b>	3.7 (Nominal)

## KEY FEATURES OF THE SL4010e RADIO

- Integrated accelerometer for optional Man Down
- Bluetooth® 4.0
- Indoor location tracking
- Integrated Wi-Fi
- Over-the-air software updates
- Upgraded audio for greater clarity at high volume
- Improved expandability
- Increased transmitter power, for greater range
- Selectable power levels

## TRANSMITTER SPECIFICATIONS

<b>4FSK Digital Modulation</b>	12.5 kHz Data: 7K60F1D and 7K60FXD
	12.5 kHz Voice: 7K60F1E and 7K60FXE
	Combination of 12.5 kHz Voice and Data: 7K60F1W
<b>Digital Protocol</b>	ETSI TS 102 361-1, -2, -3 DMR Tier II & Tier III
<b>Conducted/Radiated Emissions (TIA603D)</b>	-36 dBm < 1GHz, -30 dBm > 1GHz
<b>Frequency Stability</b>	± 1.5 ppm

## RECEIVER SPECIFICATIONS

<b>Digital Sensitivity (5% BER)</b>	0.15 uV
<b>Conducted Spurious Emissions (TIA603D)</b>	-57 dBm

## AUDIO SPECIFICATIONS

<b>Digital Vocoder Type</b>	AMBE+2™
<b>Audio Response</b>	TIA603D
<b>Rated Audio</b>	0.5 W
<b>Audio Distortion at Rated Audio</b>	3%

## BLUETOOTH SPECIFICATIONS

<b>Version</b>	4.0
<b>Range</b>	Class 2, 10 m
<b>Supported Profiles</b>	Bluetooth Headset Profile (HSP) Serial Port Profile (SPP) Motorola Solutions fast push-to-talk
<b>Simultaneous Connections</b>	1 x audio accessory and 1 x data device
<b>Permanent Discoverable Mode</b>	Optional

## Wi-Fi SPECIFICATIONS

<b>Standards Supported</b>	IEEE 802.11b, 802.11g, 802.11n
<b>Security Protocol Supported</b>	WPA, WPA-2, WEP
<b>Maximum Number of SSIDs</b>	128

## ENVIRONMENTAL SPECIFICATIONS

<b>Operating Temperature<sup>2</sup></b>	-20 °C to +60 °C
<b>Storage Temperature<sup>2</sup></b>	-30 °C to +70 °C
<b>Electrostatic Discharge</b>	IEC 61000-4-2 Level 3
<b>Dust and Water Intrusion</b>	IEC 60529 - IP54
<b>Salt Fog</b>	5% NaCl for 8 hrs at 35 C, 16 hrs standing
<b>Packaging Test</b>	MIL-STD 810D and E

<sup>1</sup> Typical battery life, 5/5/90 profile at maximum transmitter power with Bluetooth, Wi-Fi and Option Board applications disabled. 1370mAh battery rating is for 2W output.

Actual observed runtimes may vary.

<sup>2</sup> Radio only. Battery operation down to -10°C only.

• Standard feature

○ Optional feature

## CONNECTION

- UHF Band, 3 W
- Colour Screen
- Full Keypad
- 1000 Channels
- Digital Only
- Voice and Data
- Integrated Wi-Fi
- Canned Text Messaging
- Freeform Text Messaging
- Work Order Ticketing
- Bluetooth Audio
- Bluetooth Data
- Bluetooth Permanent Discoverable Mode
- Bluetooth Indoor Location Tracking
- Voice Announcement
- Text to Speech
- Option Board SL4010e
- Home Channel Reminder
- Vibrate Alert
- Ambient Light Sensor

## AUDIO

- Intelligent Audio
- SINC+ Noise Cancellation
- Acoustic Feedback Suppressor
- Microphone Distortion Control
- User-Selectable Audio Profiles
- Switch Speaker
- Trill Enhancement

## PERSONALISATION

- Wide Range of Accessories
- 2 Programmable Buttons
- Emergency Button

## MANAGEMENT

- Radio Management
- Over-the-Air Programming
  - Over-the-Air Software Update

## SAFETY

- Integrated Accelerometer
- Man Down
- Lone Worker
- Basic Privacy
- Enhanced Privacy
  - AES256 Encryption
- Transmit Interrupt (decode)
- Transmit Interrupt (encode)
- Digital Emergency
- Emergency Search Tone
- Remote Monitor
- Radio Disable / Enable
- Rated to IP54
- Rugged to MIL-STD 810

## SYSTEMS

- Direct Mode (including Dual Capacity Direct Mode)
- IP Site Connect (Single and Multi-Site)
- Capacity Plus (Single and Multi-Site)
  - Capacity Max

## MILITARY STANDARDS

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE	METHOD	PROCEDURE
<b>Low Pressure</b>	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
<b>High Temp</b>	501.1	I, II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II/A1
<b>Low Temp</b>	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
<b>Temp Shock</b>	503.1	I	503.2	A1/C3	503.3	A1/C3	503.4	I	503.5	I-C
<b>Solar Radiation</b>	505.1	II	505.2	I/Hot-Dry	505.3	I/Hot-Dry	505.4	I/Hot-Dry	505.5	I/A1
<b>Rain</b>	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, III	506.5	I, III
<b>Dust</b>	510.1	I, II	510.2	I, II	510.3	I, II	510.4	I, II	510.5	I, II
<b>Vibration</b>	514.2	VIII/F, W, XI	514.3	I/10, II/3	514.4	I/24, II/5	514.5	I/24, II/5	514.6	I/24, II/5
<b>Shock</b>	516.2	I, II	516.3	I, IV	516.4	I, IV	516.5	I, IV	516.6	I, IV

### BLUETOOTH

Connect to your radio without wires, for extra comfort and safety. A full portfolio of Bluetooth headsets and earpieces is available.



### COVERT ACCESSORIES

When you need to stay in touch discreetly, choose from our range of covert audio accessories. From clear tube earpieces to virtually invisible wireless in-ear units.



### ENERGY SOLUTIONS

Make sure your radio is powered and charged properly, with our range of energy solutions. Choose from single and multi-unit chargers, and slim and high capacity batteries.



### EARPIECES

For all-day comfort, choose from our range of earpieces. Lightweight or heavy duty, discreet or rugged, with or without built-in hearing protection.



### CARRY SOLUTIONS

However you choose to carry your SL4010e, we have a solution available. For example, the secure plastic holster protects the radio while keeping it easily to hand.



### RSMs

Make sending and receiving messages even easier with a Remote Speaker Microphone designed specifically for the SL range.



To discover how to be smartly connected, visit [www.motorolasolutions.com/mototrbo](http://www.motorolasolutions.com/mototrbo) or find your closest Motorola representative or authorised Partner at [www.motorolasolutions.com/contactus](http://www.motorolasolutions.com/contactus)

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license.

All other trademarks are the property of their respective owners. ©2020 Motorola Solutions, Inc. All rights reserved. (04-20)



**MOTOROLA SOLUTIONS**