

# SAVOX® ultra-light headsets

## SAVOX® E-C speaker unit



### User data

- for surveillance and police tasks
- adaptable to both ears
- adapts to all SAVOX PTT units



## TECHNICAL DATA

<b>Weight</b>	20 g
<b>Microphone</b>	vibration sensitive
<b>Speaker impedance</b>	according to application
<b>Cable</b>	Ø 2 mm/760 mm
<b>Connector</b>	4-pole quick release plug
<b>Operation temperature</b>	-25 to +63 °C (continuous)
<b>Supply voltage</b>	2,5–10,0 VDC
<b>ESD, EMI immunity</b>	conforms to EN 301 489-1

### OPTIONS

- direct models with in-line PTT

## SAVOX® G-C ultra-light hands-free ear set



### User data

- for surveillance and police tasks
- quick-release connector
- comfortable to wear during sustained operations
- adaptable to both ears
- no blocking of ambient sounds
- light, yet robust
- adapts to all SAVOX PTT units



## TECHNICAL DATA

<b>Weight</b>	10 g (excluding push-to-talk/switch unit)
<b>Size</b>	12 x 42 x 100 mm
<b>Microphone</b>	electret, according to application/device

### OPTIONS

- direct models with in-line PTT

## SAVOX® L-C behind-the-neck headset

IP67



### User data

- electret condenser microphone
- windscreen
- ear cushion
- adapts to all SAVOX PTT units



## TECHNICAL DATA

<b>Frequency range</b>	100 Hz to 2.5 kHz
<b>Gooseneck</b>	Ø 4 mm
<b>Cable</b>	Ø 3.6 mm
<b>Ingress protection</b>	IP 67

## Behind-the-neck headset



### User data

- electret condenser microphone
- windscreen
- adapts to all SAVOX PTT units



## TECHNICAL DATA

<b>Frequency range</b>	100 Hz to 2.5 kHz
<b>Gooseneck</b>	Ø 2.5 mm
<b>Cable</b>	Ø 2 mm