Product data sheet



FE535

Retenedor electromagnético de 490N para montaje en pared.

General

The FE535 is a VdS approved magnetic door holder with a steel, square base

A magnet for all occasions

The 500 series door holding magnets are the result of years of specialised development. With low power consumption the manets are still abel to bruduce very high holding forces. All magnets have a spring-loaded pin to ensure ejection against remnant magnetism.

Application friendly

This square steel base model offers a cost effective solution without sacrificing performance. The FE535 is supplied without keeper plate. This may be ordered separately depending on the application.

Installer friendly

For practical ease of installation, all units are complete with electrical termination. Protection diodes prevent electromagnetic pulses, and reverse polarity protection speeds up installation. The boxes are predrilled in a practical, standard format for rapid mounting.

Approvals

All models are VdS approved. (Refer to the specific device specifications)



Details

- Wall mount
- Low power
- 490 N holding power
- 100% duty cycle
- Anti-remnant ejector
- Protection diode and reverse polarity protection
- VdS approved

FE535

Retenedor electromagnético de 490N para montaje en pared.

Technical specifications

General	
Fuerza de retención N	490
(Newtons)	
Botón de liberación	No
Protección contra	Yes (diode)
inversion de polaridad	
Eléctrico	
	241/02
Tipo de fuente de	24 VCC
alimentación	
Consumo de corriente	1.5 W
Consumo de corriente	62.5 mA
Físico	
Dimensiones físicas	50 x 30 mm (Ø x H)
Entradas de cable	1
Medioambiental	
Clasificación IP	IP30
VDS Coil	
	Yes

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

